

6.

2.

The Leading Manufacturer of Non-Marring, Non-Sparking Hammers, Proudly Made in the USA, Since 1956.

۲

4.

5.

#### All of our hammers feature:

- 1. NON-SPARKING HEAD For safe use near combustible materials.
- 2. NON-MARRING HEAD Helps absorb impact and helps reduce work damage where surface protection is critical.

## 3. Cost harred shaped head

Cast barrel shaped head offers maximum striking surface while enhancing balance.

### 4. WOOD HANDLES

Our Tennessee grade-A Hickory handles are specially tapered, fire finished, with a tough urethane coating applied, providing better durability and UV protection. They have a textured handle providing a non-slip grip while striking.

#### FIBERGLASS HANDLES

 Our fiberglass handles are high visibility yellow in color and are ergonomically designed to help prevent injury from repeated use. Cushion grips provide a non-slip grip and maximum comfort while striking. Shoulder protector design prevents breaking during overstrikes.

## 6. BRASS WEDGES

The ABC brass wedge permanently secures the head to the handle and eliminates the spark danger associated with steel wedges used in other hammers.

#### Proudly Made In The USA



 $\bigcirc$ 

Making your workplace safer is as easy as ABC...

using non-sparking ABC Hammers in any high risk area where a spark can create a disaster.

3.

(1)



The Leading Manufacturer of Non-Marring, Non-Sparking Hammers, Proudly Made in the USA, Since 1956.

#### **Brass Striking Hammers**

ITEM #:	WEIGHT [LBS/KG] HANDLE HANDLE LENGTH		
ABC1BW	1.0 lbs/0.45 kg	Wood	10"
ABC2BW	2.0 lbs/0.90 kg	Wood	12.5"
<u>ABC3BW</u>	3.0 lbs/1.35 kg	Wood	12.5"
<u>ABC4BW</u>	4.0 lbs/1.80 kg	Wood	15"
ABC5BW	5.0 lbs/2.25 kg	Wood	15"
ABC3BF	3.0 lbs/1.35 kg	Fiberglass	14"
ABC4BF	4.0 lbs/1.80 kg	Fiberglass	14"
ABC5BF	5.0 lbs/2.25 kg	Fiberglass	14"

#### **Brass Sledge Hammers**

ITEM #:			HANDLE LENGTH
ABC8BW	8.0 lbs/3.60 kg	Wood	32"
ABC10BW	10.0 lbs/4.50 kg	Wood	32"
ABC12BW	12.0 lbs/5.40 kg	Wood	32"
ABC14BW	14.0 lbs/6.30 kg	Wood	32"
ABC8BF	8.0 lbs/3.60 kg	Fiberglass	33"
ABC10BF	10.0 lbs/4.50 kg	Fiberglass	33"
ABC12BF	12.0 lbs/5.40 kg	Fiberglass	33"
ABC14BF	14.0 lbs/6.30 kg	Fiberglass	33"

### **Brass Drilling Hammers**

ITEM #:	WEIGHT [LBS/KG]	HANDLE	HANDLE LENGTH
ABC2BFS	2.0 lbs/0.90 kg	Fiberglass	8"
ABC3BFS	3.0 lbs/1.35 kg	Fiberglass	8"
ABC4BFS	4.0 lbs/1.80 kg	Fiberglass	8"
ABC5BFS	5.0 lbs/2.25 kg	Fiberglass	8"

### **Brass Cut-Off Hammers**

ITEM #:	WEIGHT [LBS/KG]	HANDLE	HANDLE LENGTH
ABCWBW	2.5 lbs/1.10 kg	Wood	12"

### **Bronze/Copper Striking Hammers**

ITEM #:	WEIGHT [LBS/KG]	HANDLE	HANDLE LENGTH
ABC1BZW	1.0 lbs/0.45 kg	Wood	10"
ABC2BZW	2.0 lbs/0.90 kg	Wood	12.5"
ABC3BZW	3.0 lbs/1.35 kg	Wood	12.5"
ABC4BZW	4.0 lbs/1.80 kg	Wood	15"
ABC5BZW	5.0 lbs/2.25 kg	Wood	15"
ABC3BZF	3.0 lbs/1.35 kg	Fiberglass	14"
ABC4BZF	4.0 lbs/1.80 kg	Fiberglass	14"
ABC5BZF	5.0 lbs/2.25 kg	Fiberglass	14"

## **Bronze/Copper Sledge Hammers**

ITEM #:	WEIGHT [LBS/KG]	HANDLE	HANDLE LENGTH
ABC8BZW	8.0 lbs/3.60 kg	Wood	32"
ABC10BZW	10.0 lbs/4.50 kg	Wood	32"
ABC12BZW	12.0 lbs/5.40 kg	Wood	32"
ABC14BZW	14.0 lbs/6.30 kg	Wood	32"
ABC8BZF	8.0 lbs/3.60 kg	Fiberglass	33"
ABC10BZF	10.0 lbs/4.50 kg	Fiberglass	33"
ABC12BZF	12.0 lbs/5.40 kg	Fiberglass	33"
ABC14BZF	14.0 lbs/6.30 kg	Fiberglass	33"

### **Bronze/Copper Drilling Hammers**

ITEM #:	WEIGHT [LBS/KG]	HANDLE	HANDLE LENGTH
ABC2BZFS	2.0 lbs/0.90 kg	Fiberglass	8"
ABC3BZFS	3.0 lbs/1.35 kg	Fiberglass	8"
ABC4BZFS	4.0 lbs/1.80 kg	Fiberglass	8"
ABC5BZFS	5.0 lbs/2.25 kg	Fiberglass	8"

### Bronze/Copper Cut-Off Hammers

ITEM #:	WEIGHT [LBS/KG]	HANDLE	HANDLE LENGTH
ABCWBZW	2.5 lbs/1.10 kg	Wood	12"





5

1

2

Setting a New Standard for Dead Blow Soft Face Performance.

## DEAD BLOW HAMMERS FEATURES & BENEFITS:

#### **HOT CAST POLYURETHANE** CONSTRUCTION

Our dead blow hammers are a one piece, hot cast polyurethane construction, engineered to perform better and outlast rawhide, rubber, lead and other plastic type hammers by 10-20 times. Utilizing the benefits of polyurethane technology, no other plastic or rubber materials currently used can result in a stronger, longer lasting dead blow hammer. High visibility "Red" color makes them easier and quicker to spot on the job.

#### **2) STEEL SHOT FILLED CANISTER**

Steel shot filled canister creates a dead blow effect for sustained impact, maximum force and power, reduces or eliminates rebound and absorbs the shock on impact. The free flowing shot concentrates the intensity of the hammer strike and increases striking force by up to 40 percent. It also absorbs the blow minimizing bounce back, reducing fatigue and the risk of injury, and improving productivity.

#### **3** POLYURETHANE CONVEX STRIKING FACE

Convex faces on heads resist chipping, splitting and are cut resistant. They are designed to withstand severe striking applications. The heads provide a non marring contact surface that eliminates or minimizes denting, marring and damage to struck objects.

#### **4** STEEL REINFORCED POLYURETHANE HANDLE

Handles have a heat treated steel reinforced rod that provides added strength and safety by resisting breaking on overstrikes. The handle is fully encased in hot cast custom formulated polyurethane. The comfort design handle absorbs shock, ensures comfort and has a slip-resistant grip along with a flared end which helps prevent the hammer from slipping. Handle over-grip adds an extra layer of protection to the hot cast polyurethane construction.

#### **5** NON-SPARKING, NON-MARRING AND CHEMICAL RESISTANT

Our dead blow hammers are completely encased with unique polyurethane which eliminates any exposed metal making them spark-resistant for safe use near combustible materials. This specially formulated polyurethane resists most oil, solvents and chemicals. They are also non-marring making them the perfect tool for virtually any hammering application.

Pound For Pound, The World's Greatest Hammers.

(4



THE USA All ABC Hammers are proudly made in the USA.



The Leading Manufacturer of Non-Marring, Non-Sparking Hammers, Proudly Made in the USA, Since 1956,

## **STANDARD DEAD BLOW HAMMERS**

ITEM #	WEIGHT [OZ/LBS/KGS]	Handle Length [IN/MM]	overall length [IN/MM]	Striking face Diameter [in]	HEAD LENGTH [IN]
ABC2DB	26 oz/1.6 lbs/0.74 kg	10.5"/267mm	12.75"/324mm	2.00"	4.125"
ABC3DB	45 oz/2.8 lbs/1.28 kg	12"/305mm	14.375"/365mm	2.25"	4.625"
ABC4DB	53 oz/3.3 lbs/1.50 kg	12.5"/318mm	15.25"/387mm	2.75"	5.375"

## **SLEDGE DEAD BLOW HAMMERS**

ITEM #	Weight [Oz/lbs/kgs]	Handle Length [IN/MM]	overall length [IN/MM]	Striking face Diameter [in]	HEAD LENGTH [IN]
ABC7DB	88 oz/5.5 lbs/2.49 kg	16.5"/419mm	20"/508mm	2.75"	7"
ABC10DB	144 oz/9.0 lbs/4.08 kg	26"/660mm	30"/762mm	2.75"	7"
ABC12DB	168 oz/10.5 lbs/4.76 kg	26"/660mm	30"/762mm	3.25"	8"
ABC14DB	192 oz/12.0 lbs/5.44 kg	32"/813mm	36"/914mm	3.25"	8"

# **APPLICATIONS/INDUSTRIES**

Agriculture Aircraft Maintenance Assembly Work Automotive Custom Fabrication Construction

**DBH** 

Electrical Fire/Public Safety Foundry Operations Grain Elevators HVAC Heavy Duty Truck & Equipment Landscaping Log/Timber Home Building Machine Shop Machinery Repair Marine Motorcycle Shop Pipeline/Oil Field Plumbing Railroads Shipyards Tractor/Farm Equipment Waste Treatment Plants